

Model	Picture	Specification	Feature	Standard accessories
2G 4G FM03		2G Frequency 850/900/1800/1900 MHz 4G China/India TDD LTE:B38/B39/B40/B41 FDD LTE:B1/B3/B5/B8 WCDMA:B1/B8 GSM:900/1800MHz Europe/Middle East/Africa TDD LTE:B38/B40/B41 FDD LTE:B1/B3/B5/B7/B8/B20 WCDMA:B1/B5/B8 GSM:B3/B8 North America FDD LTE:B2/B4/B5/B12/B13/B14 WCDMA:B2/B4/B5 Australia/Taiwan/Brazil FDD LTE:B1/B3/B4/B5/B7/B8/B28 WCDMA:B1/B2/B5/B8 GSM:B2/B3/B5/B 92mm*59mm*30mm (L*W*H) Battery Capacity 5600mAh (rechargeable) Charger Supply 5 DC / 1 A Working mode: Power saving mode and normal mode GPRS Class 12 , TCP/IP Weight 200g	Geofence Real-time tracking for 15 days Standby up to 60 days Low battery alarm Built in 6 strong magnets Multiple working modes Rechargeable battery Power saving model	USB cable User manual
2G 3G 4G FM03A 6000mAh		2G-GSM 850/900/1800/1900 MHz 3G-WCDMA 800/850/900/2100MHz Frequency ①North America Version: LTE B2/B4/B12 etc.;WCDMA .B2/B5 ②Euro Version:LTE-B1 B3 B5 B7 B8 B20 etc; WCDMA:B1 B2 B5 B8 ,GSM: 850/900/1800/1900MHZ ③South American version: LTE- B1 B3 B5 B8 etc; WCDMA:B1 B8 ,GSM-900/1800MHZ 3.7V 6000mAh Location time Cold start 35s-80s;Hot start 1s Location accuracy 5 meters Operating temperature -20℃--55℃ Dimension 115*65*25mm Weight: 175/192/200g	Real-time tracking 15 days Standby up to 70 days Vibration,Displacement alert Low battery,Power off alert over speed ,Remove alert Voice monitor Geo-fence History Route Magnetic AGPS locating WIFI locating Multi working mode	Charger User manual
2G 3G 4G FM03B 10000mAh		2G-GSM 850/900/1800/1900 MHz 3G-WCDMA 800/850/900/2100MHz Frequency ①North America Version: LTE B2/B4/B12 etc.;WCDMA .B2/B5 ②Euro Version:LTE-B1 B3 B5 B7 B8 B20 etc; WCDMA:B1 B2 B5 B8 ,GSM: 850/900/1800/1900MHZ ③South American version: LTE- B1 B3 B5 B8 etc; WCDMA:B1 B8 ,GSM-900/1800MHZ 3.7V 6000mAh Location time Cold start 35s-80s;Hot start 1s Location accuracy 5 meters Operating temperature -20℃--55℃ Dimension 120*65*35mm Weight: 250/290/300g	Real-time tracking 20 days Standby up to 120 days Vibration,Displacement alert Low battery,Power off alert over speed ,Remove alert Voice monitor Geo-fence History Route Magnetic AGPS locating WIFI locating Multi working mode	Charger User manual
2G 3G 4G FM03C 2000mAh		2G-GSM 850/900/1800/1900 MHz 3G-WCDMA 800/850/900/2100MHz Frequency ①North America Version: LTE B2/B4/B12 etc.;WCDMA .B2/B5 ②Euro Version:LTE-B1 B3 B5 B7 B8 B20 etc; WCDMA:B1 B2 B5 B8 ,GSM: 850/900/1800/1900MHZ ③South American version: LTE- B1 B3 B5 B8 etc; WCDMA:B1 B8 ,GSM-900/1800MHZ 3.7V 6000mAh Location time Cold start 35s-80s;Hot start 1s Location accuracy 5 meters Operating temperature -20℃--55℃ Dimension 120*65*50mm Weight: 370/440/450g	Real-time tracking 30 days Standby up to 200 days Vibration,Displacement alert Low battery,Power off alert over speed ,Remove alert Voice monitor Geo-fence History Route Magnetic AGPS locating WIFI locating Multi working mode	Charger User manual
2G 4G Solar Power FM03F		2G -GSM Frequency 850/900/1800/1900 MHz 4G bands combination: 4G-FDD: Band 1/2/3/4/5/7/8/12/20/28A 3G-WCDMA: Band 1/2/5/8 2G-GSM: Band 2/3/5/8 Dimension 65*50*24mm Battery Capacity 9000mAh (rechargeable) Charger Supply 5 DC / 1 A Working mode: Power saving mode and normal mode GPRS Class 12 , TCP/IP Weight 249/260 g	Real time tracking; Solar power supplier Geo fence; History track; Voice monitor; waterproof, Music, Alarm LED alarm	1* Solar GPS tracker host 1* USB magnet charging cable 1* User manual 1*Collar holder (optional) 1* Magnetic holder (optional) 1*Screw holder (optional) 1* Screw driver
2G 3 year long standby FM05		Frequency 4 bands: GSM 850/900/1800/1900MHz Built in Lithium-ion battery and (3.6V, 5400mAh) and ultra-low discharge rate: less than 1%, store one year below 25℃ Power consumption Average working current <100mA, Power save current <15uA; Dimension 81mm*51mm*31mm (L*W*H) Weight 164±5g Working Temperature -20℃--70℃ Humidity 5%--95% WIFI Frequency range 2.4 GHz-2.5 GHz (2400M-2483.5M)	Long Standby time, easy to install Quick wake up, convenient to hide Strong Magnetic, removal alarm 3 years standby time(One position per day)	USB cable User manual
3G 3 year long standby FM05A		GSM: 850/900/1800/1900MHz WCDMA: 850/900/1900/2100 Built in Lithium-ion battery and (3.6V, 5400mAh) and ultra-low discharge rate: less than 1%, store one year below 25℃ Power consumption Average working current <100mA, Power save current <15uA; Dimension 81mm*51mm*31mm (L*W*H) Weight 164±5g Working Temperature -20℃--70℃ Humidity 5%--95% WIFI Frequency range 2.4 GHz-2.5 GHz (2400M-2483.5M)	Long Standby time, easy to install Quick wake up, convenient to hide Strong Magnetic, removal alarm 3 years standby time(One position per day)	USB cable User manual
NBIOT 3 year long standby FM05NB		GSM: 850/900/1800/1900MHz Cat.M1/Cat.NB1: LTE FDD B1/B2/B3/B4/B5/B8/B28 Built in Lithium-ion battery and (3.6V, 5400mAh) and ultra-low discharge rate: less than 1%, store one year below 25℃ Power consumption Average working current <100mA, Power save current <15uA; Dimension 81mm*51mm*31mm (L*W*H) Weight 164±5g Working Temperature -20℃--70℃ Humidity 5%--95% WIFI Frequency range 2.4 GHz-2.5 GHz (2400M-2483.5M)	Long Standby time, easy to install Quick wake up, convenient to hide Strong Magnetic, removal alarm 3 years standby time(One position per day)	USB cable User manual